
SPECIFICATIONS

 Model Number:
 GL24Z7
 Version:01

 Part Number:
 19039524A
 Feb 28, 2024



Mechanical Drawing:



Motor:

Nominal Voltage = 24 vdc
Operating Voltage Range = 12 - 28 vdc
Nominal Running Current = 1.30 amps
Locked Rotor Current = 3.50 amps
Running Power = 31.2 watts
Average Speed = 4100 RPM
Bearings = Ball
Air Flow = 192 ofm

Air Flow = 192 cfm Acoustic = 59.4 dBA

Construction:

Venturi: Die Cast Aluminum, Black. Propeller: Plastic, Black, UL 94V-0.

Life Expectancy:

This fan is designed for continuous duty life of 60,000 hours at 70°C.

Agency Approvals:

UL, CUL, CE

Additional Features:

Brushless DC Motor Locked Rotor Protection Reverse Polarity Protected

Operating Temperature: -10°C to 70°C Storage Temperature: -40°C to 85°C

Tachometer:

Output: 5vdc TTL Compatible

I_c: 5mA Typical

Isolated: No Pulses per Revolution: 2

Termination:

12" Lead wires, 22 AWG, UL 1061

Red – Power Black – Return

Blue/White - Tachometer Output

PQ Curve:

